



FUNCTIONS

PC connectivity and postal rates can be updated optionally from the INTERNET at a cheaper cost
All software updates can be accomplished using Exceed UK PC Program
Database of country codes for all countries (automatic Royal Mail zone lookup for country code entries)
Instant keys for selected countries for international mail services
Remote calibration of scale when necessary
Hold function allows freezing of display for a later reference
Gram, ounce, or pound/ounce display
Calculates postal fees for all popular Royal Mail and ParcelForce services for domestic and international mail including franked and metered or stamped rates (where applicable)

Basic postal services available:

- 1st Class (Letters, Large Letters, Packets)
- 2nd Class (Letters, Large Letters, Packets)

- Special Delivery by 9:00 AM (£50, £1000, £2500)
- Special Delivery by 12:00 Noon (£500, £1000, £2500)
- ParcelForce services (Monday to Friday/Saturday deliveries)
 - By 9:00 AM
 - By 10:00 AM
 - By 12:00 Noon
 - 24-hour
 - 48-hour
- Doc/Ex
- Standard Parcel
- Surface Letter (Zone 1 and 2)
- Surface Printed Papers
- Surface Small Packets
- Air Letter (Zone 1 and 2, Europe)
- Air Printed Papers (Zone 1 and 2, Europe)
- Air Small Packets (Zone 1 and 2, Europe)
- International Parcels Standard (Air)
- International Parcels Economy (Surface)

Special services available:

- Recorded
- Compensation
- Consequential Loss Fee
- International Signed For Standard and with Additional Compensation
- AirSure Standard and with Additional Compensation
- Saturday Guarantee

SPECIFICATIONS

Range	:	0 ~ 5000 grams Presence of overload stopper to prevent damage from overloading
Tare	:	Unlimited up to maximum capacity Tare Function will set negative weight to 0 without add-on.
Tare upon turning on	:	Allow tare up to max tare upon turn on, but this will not extend the measuring range on the scale.
Accuracy	:	±1% of reading ±1 digit
Calibration	:	Five points of Automatic Calibration for greater accuracy. In the event that the scale loses accuracy , recalibration may be required if the load cell of the scale is overloaded due to dropping something heavy on the scale, or dropping it.
Resolution	:	1 gram
Minimum Weight	:	1 gram
Min. Add-on Wt.	:	1 gram
Power Consumption	:	Approx 1.3 W
Power	:	100mA 15 V AC Adaptor (Supplied)
Warm-up time	:	2 seconds or less.

- Display** : Backlight 7- segment liquid crystal display, with clear protective Plastic Bezel. Displays the weight, postage, and destination code
- Auto Off** : Auto off in battery mode after 5 minutes of no Load Change. This can be changed or removed according to the customer's request.
- Temperature** : Good performance within -10 degree Centigrade to +45 degree Centigrade. The scale is designed to operate in normal room temperatures. If subjected to cold or warm temperatures, it should be allowed to reach room temperature before operating.
- Humidity** : Performs to OIML standards within humidity range from 20% to 95% (non-condensing).
- Case & Platform** : Fold-up platform for weighing large flats. Fine texture ABS plastic or equivalent material
- Load Cell Technology** : Temperature compensated 2024 – T4/T351 Aluminum Alloy Material
- Rate Change** : Easily Replaceable Rate Change Chip or Optional Chip Update from the Internet

KEYS

- Beeping** : Audible beep
- Technology** : Membrane keyboard
- Quantity** : 45

KEYBOARD LAYOUT



PHYSICAL FEATURES

Dimensions : 9.5in. x 7.7in x 2.71in
Platform Size : 7.5in x 5.1in
Weight : 1080g (2lb 6.1oz) scale only

PACKAGING

Box Dimension : 13.6in x 10.0in x 3.75in
Packaged Weight : 1.80kg (4lbs, 1.80oz)
Master Carton Dimension : 28.3in x 20.1in x 20.1in
Quantity: 20 boxes per Master carton
Volume: 0.187cbm
Gross Weight: 18.50kg
IATA Dimensional Weight: 21.50kg

WARRANTY

1 year from date of sale to end-user against defect in manufacturing and materials

XIAMEN ELANE ELECTRONICS