

**FEATURES & FUNCTIONS**

- Highly-accurate, electronic digital weighing scale
- With Tare feature for weighing items using a container

SPECIFICATIONS

Range	: 0 ~ 10lbs. Mechanical overload protection
Tare	: Unlimited up to scale's maximum capacity but will not extend the range of the load cell. 0 Weight No Tare Function.
Negative weight	: Tare Function will set negative weight to 0 without add-on.
Tare upon turning on	: Allow tare up to max tare upon turn on, but this will not extend the measuring range on the scale.
Accuracy	: $\pm 0.1\%$ of reading ± 1 digit

Calibration	: Four points of Automatic Calibration for greater accuracy
Resolution	: 0.1 oz
Minimum Weight	: 0.1 oz
Min. Add-on Wt.	: 0.1 oz
Power	: AC Adaptor – 9V, 100mA (Supplied) 9V Alkaline battery (Not supplied)
Auto Off	: Auto off after 5 minutes of non-use in battery operation
Warm-up time	: 1 minute or less
Display	: 7-segment LCD with 3 + 2 half digits
Temperature	: Good performance within -10 degree Centigrade to +45 degree Centigrade. The scale is designed to operate in normal room temperatures. If subjected to cold or warm temperatures, it should be allowed to reach room temperature before operating.
Case & Platform	: Fine textured ABS plastic or equivalent
Load Cell Technology	: Four optimal placed single strain gages with temperature compensation
Load Cell Body	: High Tensile Strength Aluminum Alloy

PHYSICAL FEATURES

Dimensions	: 7 ³ / ₄ " x 5 ¹ / ₂ " x 2 ¹ / ₄ "
Platform Size	: 5 ¹ / ₂ " x 5" with fold up platform to weigh the large letters.
Weight	: 1lb 2.8oz Without AC adapter

KEYS

Technology	: Clicker Switch
Quantity	: 2

KEYBOARD LAYOUT



PACKAGING

Box Dimension	: 11" x 6 $\frac{1}{4}$ " x 3 $\frac{1}{4}$ "
Packaged Weight	: 2lbs 4oz
Master Carton Dimension	: 23 $\frac{1}{2}$ " x 18 $\frac{1}{2}$ " x 12 $\frac{1}{4}$ "
	Quantity: 20 boxes per Master carton
	Volume: 0.09 cbm
	Gross Weight: 42 lbs
	IATA Dimensional Weight: 33 lbs