

RoHS
Lead-Free Soldering



FEATURES

- Large capacity highly-accurate postal scale (10lb/0.1oz)
- Has 3 types of power supply: USB power from PC, batteries, or adapter
- USB power from PC – plug and play (no software needed)
- USB connection (USB cable supplied)
- Can be used with online postage system such as Stamps.com, USPS, Endicia, and USA PC Postal Calculator to capture weight reading to PC
- With hinged platform that allows weighing of large envelopes vertically or mailing tubes
- Clear large LCD display

SPECIFICATIONS

Range : 0-10lb
Mechanical overload protection

Accuracy : $\pm 0.1\%$ of reading ± 1 digit

Resolution : 0.1oz

4th floor, #10 of Ai-De Air Industry Park,
Gao Qi South 12th Road, Xiamen, Fujian 361006, China
Tel: (86) 592-602-3169 Fax: (86)592-566-5162
Email: sales@elane.net
Website: www.elane.net

Minimum Weight	: >0.1oz
Min. Add-on Wt.	: >0.1oz
Power	: USB power 9V alkaline battery (not supplied) 9V AC Adapter (optional)
Warm-up time	: 2 seconds or less.
Battery Low	: Displays LO on LCD
User Calibration	: Using 5lbs weights (not supplied)
Display	: Large 5-digit LCD
Temperature	: Good performance within 30 degree to 100 degree Fahrenheit. The scale is designed to operate in normal room temperatures. If subjected to cold or warm temperatures, it should be allowed to reach room temperature before operating.
Case & Platform	: Fine texture ABS plastic
Load Cell Technology	: Four element single strain gage with temperature compensation
Load Cell Body	: Material: 2024 – T4/T351 Aluminum Alloy
Interface	: Includes USB cable to connect to PC

PHYSICAL FEATURES

Dimensions	: 7 ³ / ₄ " x 5 ¹ / ₂ " x 2 ¹ / ₄ "
Platform Size	: 5 ¹ / ₂ " x 5" with fold up platform to weigh the large letters.
Weight	: 1lb 2.8oz Without AC adapter

KEYS

Technology	: Clicker Switch
Quantity	: 2

KEYBOARD LAYOUT



PACKAGING

Box Dimension : 11" x 6¼" x 3¼"
Packaged Weight : 2lbs 4oz
Master Carton Dimension : 23½" x 18½" x 12¼"
Quantity: 20 boxes per Master carton
Volume: 0.09 cbm
Gross Weight: 42 lbs
IATA Dimensional Weight: 33 lbs

WARRANTY

1 year from date of sale to end-user against defect in manufacturing and materials.