



FUNCTIONS

- Highly-accurate, electronic digital weighing scale
- With Tare feature for weighing items using a container

SPECIFICATIONS

Range	: 0 ~ 22lbs. Mechanical overload protection
Tare	: Unlimited up to scale's maximum capacity but will not extend the range of the load cell. 0 Weight No Tare Function.
Negative weight	: Tare Function will set negative weight to 0 without add-on.
Tare upon turning on	: Allow tare up to max tare upon turn on, but this will not extend the measuring range on the scale.
Accuracy	: $\pm 0.1\%$ of reading ± 1 digit

Calibration	: Four points of Automatic Calibration for greater accuracy
Resolution	: 0.1 oz
Minimum Weight	: 0.1 oz
Min. Add-on Wt.	: 0.1 oz
Power	: AC Adaptor UL listed: 9 V, 100mA (Supplied) Battery: 6 x 1.5V AA Alkaline batteries (Not supplied)
Auto Off	: Auto off after 5 minutes of non-use in battery operation
Warm-up time	: 1 minute or less
Display	: 7-segment LCD with 5 digits
Temperature	: Good performance within -10 degree Centigrade to +45 degree Centigrade. The scale is designed to operate in normal room temperatures. If subjected to cold or warm temperatures, it should be allowed to reach room temperature before operating.
Case & Platform	: Fine textured ABS plastic or equivalent
Load Cell Technology	: Optimal placed single strain gages with temperature compensation
Load Cell Body	: High Tensile Strength Aluminum Alloy

PHYSICAL FEATURES

Dimensions	: 26.5cm X 20cm X 8.3cm
Platform Size	: 20cm x 15cm
Weight	: 1134g without Batteries

KEYS

Technology	: Clicker Switch
Quantity	: 2

KEYBOARD LAYOUT



PACKAGING

Box Dimension : 40cm X 26.5cm X 9.8cm
Packaged Weight : 1.80kg (4lbs 1.80oz)
Master carton Dimension: 55.0cm X 52.0cm X 43.0cm
Quantity: 10 boxes per Master carton
Volume: 0.13 cbm
Gross Weight: 18.50 kg (42 lbs, USA only)
IATA Dimensional Weight: 21.50kg (48 lbs, USA only)